




**Wainwright
Instruments GmbH**

Widdersberger Str.14
D82346 Andechs, Germany
 Tel.: +49-8152-918230 Fax: +49-8152-918255
 E-Mail: info@wainwright-filters.com
 Internet: www.wainwright-filters.com


**6 Resonator
Cavity Design
WRCA Series**

Tunable Notch Filter
800 to 960 MHz


**Model No.
WRCA800/960-0.2/40-6...**
(add codes - see below)




Tuned to the low end



Tuned to 920 MHz



Tuned to the high end



Model **WRCA 800/960-0.2/40-6EEK**



approx. Weight:
10.5 kg (23.1 lbs.)

Available with Tuning Knobs or Screwdriver-Tunable

This filter is similar to the design of the customer specified Fo models. It will produce up to 6 notches in the passband. The notch Fo is determined by the user by tuning each resonator. Each notch is very narrow and has 5 to 10 dB reject attenuation. Several notches can be combined by tuning them to the same frequency. This increases the notch depth and width. Attenuation will be greater at the low end of the tuning range and less at the upper end. The filter is designed to produce a 200 kHz bandwidth with at least 40 dB reject attenuation when all notches are tuned to 920 MHz. The temperature specification of +15° to +40°C applies to this frequency and stability decreases away from the center towards both ends of the range. Each filter is tested over the full range and 4 curves (as shown above) are supplied on delivery.

Specifications	Model No. WRCA 800/960-0.2/40-6.....		Add connector code (SS or EE) and option code (K or SD)
Tuning Range:	800 to 960 MHz		
Passband Loss:	1.0 dB max. Dc to 2000 MHz - <u>except</u> 2.0 dB max. at Fo ± 600 kHz notch corners		
Return Loss (50 Ω):	14 dB min. (17 dB typical) = VSWR 1.5 : 1 max. (1.33 : 1 max. typical)		
Notch attenuation:	40 dB min. at Fo (920 MHz) ± 100 kHz		
Oper. Temperature:	+15°C to +40°C		
Connector Codes:	SMA-female = SS or N-female = EE - both on <u>one</u> 107 x 410 mm surface		
Options Codes:	Filters with tuning knobs = K - Filters with slots for screwdriver tuning = SD		
Mounting Provision:	4 x M4 threaded holes each on all sides - see drawing UMP-1 (Website)		
Dimensions:	107 mm high (plus tuning knobs) x 275 (plus connectors) x 410 mm		
Price Basis: see Ord.Inf., Terms, Warranty	PRICES:	Euro: Price based on shipment ex factory	US-\$: Price includes shipping, import Charges and customs duty. *
When purchasing	1 - 4 pcs.	€1.735,--	\$ 2,650.--
Test Sheet with Analyzer Curves supplied.			
* Prices in US-\$ for shipments to the USA only. American customers are welcome to purchase at EURO-prices and carry postage/freight and import charges directly.			

Delivery Time: normally 4 to 6 weeks - depending on work load in the factory at time of order.