




**Wainwright
Instruments GmbH**


Widdersberger Str.14
D82346 Andechs, Germany
 Tel.: +49-8152-918230 Fax: +49-8152-918255
 E-Mail: info@wainwright-filters.com
 Internet: www.wainwright-filters.com

7 Resonator Cavity Design WRCG Series	Band Reject Filter Reject Band 925 to 960 MHz Passbands DC to 910 & 975 to 2400 MHz	Model Number: WRCG-925/960-910/975-30/7 (add connector code - see below)
---	--	--



Model Numbers: WRCG 925/960-910/975-30/7SS (= SMA-F)
 WRCG 925/960-910/975-30/7EE (= N-F)

- **Very Flat Passband to 2400 MHz**
- **Slopes: 15 MHz / 30 dB**



Dimensions:
 95 mm high x 30 mm wide
 220 mm long – plus connectors

Approx. Weight: 0.9 kg (1.9 lbs.)



Specifications			
Reject Band:	925 to 960 MHz		
Reject Attenuation:	30 dB min.		
Passbands:	DC to 910 MHz and 975 to 2400 MHz		
Return Loss (50Ω) in Passband:	14 dB min. = VSWR 1.5 : 1 max.		
Passband Loss:	1.5 dB max. <u>except:</u> 2.0 dB max. at corners (910 MHz and 975 MHz)		
Operating Temperature:	+15°C to +40°C		
Dimensions and approx. weight:	95 mm high x 30 x 220 mm plus connectors		Approx. Weight: 0.9 kg (1.9 lbs)
Mounting Provision:	4 x M4 threaded holes each on all sides - see drawing UMP-1		
Connector Code:	SMA-female = SS or N-female = EE		
Price Basis: see Ord. Inf., Terms, Warranty	PRICES:	Euro: Price based on shipment ex factory	US-\$: Price includes shipping, import charges and customs duty. *
When purchasing	1 – 4 pcs.	€ 856,--	\$ 1330.--
Test Sheet with Analyzer Curves supplied.			
* Prices in US-\$ for shipments to the USA only. American customers are welcome to purchase at EURO-prices and carry postage/freight and import charges directly.			

Delivery Time: normally 3 to 4 weeks - depending on work load in the factory at time of order.