




**Wainwright
Instruments GmbH**


Widdersberger Str.14
D82346 Andechs, Germany
 Tel.: +49-8152-918230 Fax: +49-8152-918255
 E-Mail: info@wainwright-filters.com
 Internet: www.wainwright-filters.com

8 Resonator Cavity Design WRCG Series	<h2>Band Reject Filter</h2> <p>Reject Band 1710 to 1785 MHz Passbands DC to 1680 & 1805 to 4000 MHz</p>	Model Number: WRCG-1710/1785-1680/1805-35/8 (add connector code - see below)
---	--	---



Model Numbers: WRCG 1710/1785-1680/1805-35/8SS (= SMA-F)
 WRCG 1710/1785-1680/1805-35/8EE (= N-F)

- **Very Flat Passband to 4000 MHz**
- **Slopes 30/20 MHz - 35 dB**



Dimensions:
 60 mm high x 30 mm wide
 215 mm long – plus connectors

Approx. Weight: 0.7 kg (1.5 lbs.)



Specifications			
Reject Band:	1710 to 1785 MHz		
Reject Attenuation:	35 dB min.		
Passbands:	DC to 1680 MHz and 1805 to 4000 MHz		
Passband Loss:	0.7 dB max. / 1.0 dB max. at passband corners		
Return Loss (50Ω) in Passband:	14 dB min. = VSWR 1.5 : 1 max.		
Operating Temperature:	+15°C to +40°C		
Dimensions:	60 mm high x 30 x 215 mm plus connectors		Approx. Weight: 0.7 kg (1.5 lbs)
Mounting Provision:	4 x M4 threaded holes each on all sides - see drawing UMP-1 (Website)		
Connector Code:	SMA-female = SS or N-female = EE		
Price Basis: see Ord. Inf., Terms, Warranty	PRICES:	Euro: Price based on shipment ex factory	US-\$: Price includes shipping, import charges and customs duty. *
When purchasing	1 – 4 pcs.	€872,--	\$ 1355.--
Test Sheet with Analyzer Curves supplied.			
* Prices in US-\$ for shipments to the USA only. American customers are welcome to purchase at EURO-prices and carry postage/freight and import charges directly.			

Delivery Time: normally 3 to 4 weeks - depending on work load in the factory at time of order.