





**Wainwright
Instruments GmbH**

Widdersberger Str.14
D82346 Andechs, Germany
 Tel.: +49-8152-918230 Fax: +49-8152-918255
 E-Mail: info@wainwright-filters.com
 Internet: www.wainwright-filters.com

12+9 Resonator Ultra Stable Cavity Design	Band Reject Filter	Model Number: WRCTF-870/880-868/882-80/ 12+9
WRCTF Series	Reject Band 870 to 880 MHz Passbands DC to 868 & 882 to 2400 MHz	(add connector code - see below)



Model Numbers: WRCTF 870/880-868/882-80/12+9SS (= SMA-F) OR: WRCTF 870/880-868/882-80/12+9EE (= N-F)



approx. weight: 9.1 kg (20 lbs.)

Dimensions:
 107 mm high x 240 mm wide
 240 mm long – plus connectors



- 1 Step Slopes: 2 MHz / 80 dB**
- 1 Ultra Stable**
- 1 Very Flat Passband to 2400 MHz**

Specifications			
Reject Band:	870 to 880 MHz		
Reject Attenuation:	80 dB min.		
Passbands:	DC to 868 MHz and 882 to 2400 MHz		
Passband Loss:	2 dB max. <u>except:</u> 4 dB max. at passband corners		
Return Loss (50Ω) in Passband:	14 dB min. = VSWR 1.5 : 1 max.		
Operating Temperature:	+15°C to +40°C		
Dimensions & approx. Weight:	107 mm high x 240 x 240 mm plus connectors	Approx. Weight: 9.1 kg (20 lbs)	
Mounting Provision:	4 x M4 threaded holes each on all sides - see drawing UMP-1 (Website)		
Connector Code:	SMA-female = SS or N-female = EE - both connectors on <u>one</u> 107 x 240 mm surface		
Price Basis: see Ord. Inf., Terms, Warranty	PRICES:	Euro: Price based on shipment ex factory	US-\$: Price includes shipping, import charges and customs duty. *
When purchasing	1 – 4 pcs.	€3.388,--	Will be quoted.
Test Sheet with Analyzer Curves supplied.			
* Prices in US-\$ for shipments to the USA only. American customers are welcome to purchase at EURO-prices and carry postage/freight and import charges directly.			

Delivery Time: normally 4 to 6 weeks - depending on work load in the factory at time of order.