



Absorptive Filter (BP/BR)

WACGV12+12-DC-822/832-862/872-2300-50/60S3

Passband 1: DC to 822 MHz


Passband 2: 832 to 862 MHz

Passband 3: 872 to 2300 MHz


Passband	Band 2 (Band Pass)	Band 1 & 3 (Band Reject)
Insertion Loss	832 to 862 MHz	DC to 822 MHz && 872 to 2300 MHz
Return Loss	3 dB max.	2 dB max.
Stopbands	14 dB min.	14 dB min.
Stopband Attenuation	DC to 822 & 872 to 2300 MHz	832 to 862 MHz
Operating Temperature	50 & 50 dB min.	60 dB min.
Power Handling	15 °C to 45 °C	
Dimensions (L x W x H)	max. 100 W CW into a 2:1 VSWR (See our warranty)	
Approx. Weight	max. 385 x 60 x 130 mm (connectors may protrude)	
Mounting Provision	4.25 kg	
Connector Common	10 mm Flanges on both ends with 3.3 mm holes	
Connector 1	SMA - Female	
Connector 2	SMA - Female	

Typical Performance

12+12 Section Cavity Design



Technical drawing



Connector Options:

SMA - Female
SMA - Male
N - Female

Unit prices

1-4 pieces
4480 €

5-9 pieces
4256 €

10-24 pieces
4032 €

25-49 pieces
3808 €

50-99 pieces
3584 €

100- pieces
3360 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711