

# Band Pass Filter WBCDB3-444.5-463.5-466.5-485.5-50SS

Passband 463.5 to 466.5 MHz Slopes 19 MHz Bandwidth 3 MHz Attenuation 50 dB min.

Passband $465 (Fo) \pm 1.5 \text{ MHz} = 463.5 \text{ to } 466.5 \text{ MHz}$ Insertion Loss0.5 dB max. at Fo (0.6 dB max. at Corners)

**Return Loss** 14 dB min. (VSWR 1.5:1 max.)

**Stopband** DC to 444.5 MHz and 485.5 to 1200 MHz

Stopband Attenuation50 dB min.Operating Temperature15 °C to 45 °C

Power Handling will be quoted on request (See our <u>warranty</u>)


Dimensions (L x W x H) max. 255 x 75 x 175 mm (connectors may protrude)

Approx. Weight 3.75 kg

**Mounting Provision** 7.5 mm flanges on both ends with 5.2 mm holes

Connector 1SMA - FemaleConnector 2SMA - Female


### **Typical Performance**



## 3 Section Cavity Design



#### **Technical drawing**



#### **Connector Options:**

SMA - Female SMA - Male N - Female N - Male BNC - Female BNC - Male 7/16" - Female

 Unit prices
 1-4 pieces
 5-9 pieces
 10-24 pieces

 3390 €
 3221 €
 3051 €

**24 pieces 25-49 pieces** 1 € 2882 €

**50-99 pieces** 2712 €

**100+ pieces** 2543 €

#### **Delivery Terms**

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.

82346 Andechs Germany Phone: +49 (0) 8152 918230 Telefax: +49 (0) 8152 918255 Email: info@wainwright-filters.com

#### Legal notes

Managing director: Terence Wainwright Registering court: Amtsgericht München Abt.B Nr. 58192 VAT Id number: DE 128249711