

# Band Pass Filter WBCJV4-2368.5-2438.5-2458.5-2528.5-40SS

Passband 2438.5 to 2458.5 MHz Slopes 70 MHz Bandwidth 20 MHz Attenuation 40 dB min.

Passband $2448.5 (Fo) \pm 10 \text{ MHz} = 2438.5 \text{ to } 2458.5 \text{ MHz}$ Insertion Loss1.25 dB max. at Fo (1.5 dB max. at Corners)

**Return Loss** 14 dB min. (VSWR 1.5:1 max.)

**Stopband** DC to 2368.5 MHz and 2528.5 to 6370 MHz

Power Handling will be quoted on request (See our <u>warranty</u>)

Dimensions (L x W x H) max. 100 x 20 x 45.5 mm (connectors may protrude)

Approx. Weight 0.2 kg

**Mounting Provision** 7.5 mm flanges on both ends with 3.3 mm holes

Connector 1SMA - FemaleConnector 2SMA - Female


## **Typical Performance**

### 2438.5 MHz 1.5 dB 2368.5 MHz 40 dB DC 2458.5 MHz 2528.5 MHz 40 dB 6370 MHz

# 4 Section Cavity Design



## **Technical drawing**



#### **Connector Options:**

SMA - Female SMA - Male N - Female N - Male BNC - Female BNC - Male

**Unit prices** 

**1-4 pieces** 1290 €

**5-9 pieces** 

10-24 pieces

**25-49 pieces** 1097 €

**50-99 pieces** 1032 €

**100+ pieces** 968 €

## **Delivery Terms**

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.

Graf-Rasso-Street. 1 82346 Andechs Germany Phone: +49 (0) 8152 918230 Telefax: +49 (0) 8152 918255 Email: info@wainwright-filters.com

Managing director: Terence Wainwright Registering court: Amtsgericht München Abt.B Nr. 58192 VAT Id number: DE 128249711