



Band Reject / Notch Filter

WRCGV12-762-772-792-802-70SS

Stopband 772 to 792 MHz


Slopes 10 MHz

Bandwidth 20 MHz

Attenuation 70 dB min.

Passband	DC to 762 MHz and 802 to 2190 MHz
Insertion Loss	1.25 dB max. (2 dB max. at Corners)
Return Loss	14 dB min. (VSWR 1.5:1 max.)
Stopband	782 (Fo) $\pm$ 10 MHz = 772 to 792 MHz
Stopband Attenuation	70 dB min.
Operating Temperature	15 °C to 45 °C
Power Handling	will be quoted on request (See our warranty)
Dimensions (L x W x H)	max. 385 x 30 x 105 mm (connectors may protrude)
Approx. Weight	1.95 kg
Mounting Provision	10 mm flanges on both ends with 3.3 mm holes
Connector 1	SMA - Female
Connector 2	SMA - Female


Typical Performance



12 Section Cavity Design



Technical drawing



Connector Options:

SMA - Female
N - Female

Unit prices

1-4 pieces
1890 €

5-9 pieces
1796 €

10-24 pieces
1701 €

25-49 pieces
1607 €

50-99 pieces
1512 €

100+ pieces
1418 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711