




Band Reject / Notch Filter

WRCGV12-2112.5-2122.5-2142.5-2152.5-75SS


Stopband 2122.5 to 2142.5 MHz Slopes 10 MHz Bandwidth 20 MHz Attenuation 75 dB min.

Passband	DC to 2112.5 MHz and 2152.5 to 4000 MHz
Insertion Loss	1 dB max. (2.5 dB max. at Corners)
Return Loss	14 dB min. (VSWR 1.5:1 max.)
Stopband	2132.5 (Fo) $\pm$ 10 MHz = 2122.5 to 2142.5 MHz
Stopband Attenuation	75 dB min.
Operating Temperature	15 °C to 45 °C
Power Handling	will be quoted on request (See our warranty)
Dimensions (L x W x H)	max. 325 x 30 x 56 mm (connectors may protrude)
Approx. Weight	1.1 kg
Mounting Provision	10 mm flanges on both ends with 3.3 mm holes
Connector 1	SMA - Female
Connector 2	SMA - Female

Typical Performance




12 Section Cavity Design



Technical drawing

©2013 Wainwright Instruments. All rights reserved.



Connector Options:

SMA - Female
N - Female

Unit prices	1-4 pieces	5-9 pieces	10-24 pieces	25-49 pieces	50-99 pieces	100+ pieces
	1890 €	1796 €	1701 €	1607 €	1512 €	1418 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711