


Attenuation 40 dB min.

Passband	DC to 702.5 MHz and 712.5 to 1990 MHz
Insertion Loss	0.6 dB max. (1.25 dB max. at Corners)
Return Loss	15 dB min. (VSWR 1.43:1 max.)
Stopband	707.5 (Fo) $\pm$ 2.5 MHz = 705 to 710 MHz
Stopband Attenuation	40 dB min.
Operating Temperature	15 °C to 45 °C
Power Handling	will be quoted on request (See our warranty)
Dimensions (L x W x H)	max. 270 x 120 x 108 mm (connectors may protrude)
Approx. Weight	4.8 kg
Mounting Provision	15 mm flanges on both ends with 5.2 mm holes
Connector 1	SMA - Female
Connector 2	SMA - Female

8 Section Cavity Design



Technical drawing



SMA - Female
SMA - Male
N - Female
N - Male
BNC - Female
BNC - Male

Unit prices	1-4 pieces	5-9 pieces	10-24 pieces	25-49 pieces	50-99 pieces	100+ pieces
	2290 €	2176 €	2061 €	1947 €	1832 €	1718 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
 Managing director: Terence Wainwright
 Registering court: Amtsgericht München Abt.B Nr. 58192
 VAT Id number: DE 128249711