




Diplexer/Duplexer (BP/HP)

WDJ16+9-450-960/1300-4000-90/50E3


Passband 1: 450 to 960 MHz Passband 2: 1300 to 4000 MHz

Passbands	Band 1 (Band Pass)	Band 2 (High Pass)
	450 to 960 MHz	1300 to 4000 MHz
Insertion Loss	1 dB max.	1 dB max.
Return Loss	15 dB min.	15 dB min.
Stopbands	DC-375 & 1300-4000 MHz	DC to 960 MHz
Stopband Attenuation	50 & 50 dB min.	90 dB min.
Operating Temperature	15 °C to 45 °C	
Power Handling	max. 100 W CW into a 2:1 VSWR (See our warranty)	
Dimensions (L x W x H)	max. 125 x 54 x 21 mm (connectors may protrude)	
Approx. Weight	0.4 kg	
Mounting Provision	7.5 mm flanges on both ends	
Connector Common	N - Female	
Connector 1	N - Female	
Connector 2	N - Female	


Typical Performance



16+9 Section LC Design



Technical drawing



©2015 Wainwright Instruments. All rights reserved.

Connector Options:
N - Female

Unit prices	1-4 pieces	5-9 pieces	10-24 pieces	25-49 pieces	50-99 pieces	100+ pieces
	1880 €	1786 €	1692 €	1598 €	1504 €	1410 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711