




Diplexer/Duplexer (LP/HP)

WDKX11+10-DC-4500/5150-15000-40S3


Passband 1: DC to 4500 MHz Passband 2: 5150 to 15000 MHz

	Band 1 (Low Pass)	Band 2 (High Pass)
Passbands	DC to 4500 MHz	5150 to 15000 MHz
Insertion Loss	1.5 dB max.	2 dB max.
Return Loss	14 dB min.	12 dB min.
Stopbands	5150 to 15000 MHz	DC to 4500 MHz
Stopband Attenuation	40 dB min.	40 dB min.
Operating Temperature	15 °C to 45 °C	
Power Handling	max. 5 W CW into a 2:1 VSWR (See our warranty)	
Dimensions (L x W x H)	max. 45 x 27 x 12.7 mm (connectors may protrude)	
Approx. Weight	0.07 kg	
Mounting Provision	4 x M2.5 threaded holes in base	
Connector Common	SMA - Female	
Connector 1	SMA - Female	
Connector 2	SMA - Female	


Typical Performance



11+10 Section LC Design



Technical drawing



Connector Options:
SMA - Female
SMA - Male

Unit prices	1-4 pieces	5-9 pieces	10-24 pieces	25-49 pieces	50-99 pieces	100+ pieces
	1860 €	1767 €	1674 €	1581 €	1488 €	1395 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711