



Manually Tunable Band Reject / Notch Filter

WTRCTW10-2000-2700-1.6-6-40SSK

Tuning Range 2000 to 2700 MHz


Bandwidth 1.6 MHz

Slopes 2.2 MHz

Attenuation 40 dB min.

Passband	DC to Fo - 3 MHz and Fo + 3 to 4000 MHz
Insertion Loss	1.25 dB max. (2 dB max. at Corners)
Return Loss	14 dB min. (VSWR 1.5:1 max.)
Stopband	1.6 MHz bandwidth tunable from 2000 to 2700 MHz
Stopband Attenuation	40 dB min.
Operating Temperature	15 °C to 45 °C
Power Handling	will be quoted on request (See our warranty)
Dimensions (L x W x H)	max. 330 x 120 x 76 mm (connectors may protrude)
Approx. Weight	5.8 kg
Mounting Provision	15 mm flanges on both ends with 5.2 mm holes
Connector 1	SMA - Female
Connector 2	SMA - Female
Tuning	Tuning with knobs


Typical Performance



10 Section Cavity Design



Technical drawing



Connector Options:

SMA - Female
SMA - Male
N - Female
N - Male
BNC - Female
BNC - Male

Unit prices

1-4 pieces
3290 €

5-9 pieces
3126 €

10-24 pieces
2961 €

25-49 pieces
2797 €

50-99 pieces
2632 €

100+ pieces
2468 €

Delivery Terms

FCA Andechs (free carrier) according to Incoterms 2020. Regarding payment terms and warranty see Terms and Conditions. Delivery time: normally 4 to 6 weeks - depending on quantity ordered and on our work load. **Customer is responsible for observing all applicable export laws in regard to filter application and location of end user.**

Wainwright Instruments GmbH
Graf-Rasso-Street. 1
82346 Andechs
Germany

Contact
Phone: +49 (0) 8152 918230
Telefax: +49 (0) 8152 918255
Email: info@wainwright-filters.com

Legal notes
Managing director: Terence Wainwright
Registering court: Amtsgericht München Abt.B Nr. 58192
VAT Id number: DE 128249711